LIUGONG



Overall Lift Capacity Max. Overall Width Overall Length Overall Weight

14 / 9.5 m (45'11" / 31'2") 320 kg (705 lb) 1.19 m (3'10") 2.49 m (8'2") 3,020 kg (6,657 lb)


LS1212H

LS1212H Electric Scissor Lift H-Drive

LIUGONG

TOUGH WORLD. TOUGH EQUIPMENT.

LS1212H SPECIFICATIONS >>>







DIMENSIONS	
A. Working Height Max. (Indoor/Outdoor)	14 / 9.5 m (45'11" / 31'2"
B. Platform Height Max. (Indoor/Outdoor)	12 / 7.5 m (39'4" / 24'7"
C. Platform Height (Stowed)	1.48 m (4'10"
D. Platform Length	2.28 m (7'6")
E. Platform Width	1.15 m (3'9"
F. Extension Deck (Roll Out)	0.9 m (2'11"
G. Overall Length	2.49 m (8'2"
H. Overall Length (Without Ladder)	2.29 m (7'6"
I. Overall Width	1.19 m (3'10"
J. Stowed Height (Rails Up)	2.63 m (8'8"
K. Stowed Height (Rails Down)	2.07 m (6'9"
L. Wheelbase	1.88 m (6'2"
M. Ground Clearance (Pothole Raised)	100 mm (4"
N. Ground Clearance (Pothole Deployed)	20 mm (0.8"

PRODUCTIVITY	
Overall Lift Capacity Max.	320 kg (705 lb)
Extension Deck Capacity	120 kg (264 lb)
Platform Occupancy Max. (Indoor/Outdoor)	2 / 1
Drive Speed (Stowed)	2 km/h (1.2 mph)
Drive Speed (Raised)	0.4 km/h (0.2 mph)
Turning Radius (Inside/Outside)	0.24 / 2.39 m (9" / 7'10")
Lift/Lower Time	59 / 46 s
Gradeability	25 %
Tilt Sensor Activation	X 1.5° / Y 3°
Tire Size (Solid Non-marking)	381 x 127 mm (1'3" x 5")

POWER	
Battery	24 V / 225 Ah
Lithium Battery (Optional)	24 V / 230 Ah
Charger	24 V / 30 A
Lift Motor	24 V / 3.3 kW
Hydraulic System Volume	25 L (6 gal 4 pt)
Hydraulic Tank Capacity	20 L (5 gal)
WEIGHT	

Overall Weight

3,020 kg (6,657 lb)

Guangxi Liugong Machinery Co., Ltd. No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China T: +86 772 3886124 E: overseas@liugong.com www.liugong.com 10/2024 Designed by LiuGong

Specifications and designs are subject to change without notice. Machines shown may include optional equipment. LiuGong standard and optional equipment may vary from region to region. Please consult your LiuGong dealer for information specific to your area.